

RING Honeycomb matting

16/07/2014



STANDARD MATTING

FEATURES

Honeycomb design.
Non-slip surface.
Open or closed.

ADVANTAGES

- Non-slippery
- Thermal and acoustic insulation
- Noise, vibration, and cold propagation reduction
- High damping and insulation power
- Reduces tiredness and helps to increase productivity
- Mud-removing
- Easy to take up and clean
- Suitable to be used with wet and cold floors

BENEFITS

- Safety
- Comfort
- Performance
- Economy
- Cleanliness

APPLICATIONS

Heavy transit areas.


Floor mats at work stations.

The open variety has been developed for self-draining, and is especially appropriate for swimming pools, health resorts, beach areas, or any place where drainage is required.


www.trelleborg.com/elastomerlaminates

MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

	Measured characteristics	Standard	Value
MECHANICAL			
	<i>Rubber compound</i>		SBR
	<i>Hardness</i>	ASTM D2240	70 ±5 Shore A
	<i>Abrasion resistance (5N)</i>	ISO 4649	≤250 mm ³
PROFILE			PATTERN



Honeycomb (MH)
open



Honeycomb (MH)
closed

DIMENSIONS

Colour	Thickness (mm)		Width (mm)		Length (m)		Weight (kg/m ²)	Pattern
●	14	±1	1000	±2%	1.8	±2%	8	MH open
●	22	±1.75	800	±2%	1.2	±2%	15	MH open
●	22	±1.75	1000	±2%	1.5	±2%	15	MH open
●	14	±1	1000	±2%	1.8	±2%	9.5	MH closed

IDENTIFICATION

<i>Branding</i>	Without.
<i>Back face</i>	With support pivot pins.
<i>Packaging</i>	Laid onto the pallet.
<i>Wrapping</i>	Black polyethylene film.
<i>Labelling</i>	Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability.