



B.P.
20/38 bar

APPLICATIONS


- Watering
- Irrigation
- Water supply and delivery

SECTORS OF ACTIVITY

- Farms
- Vegetable growers, horticulture
- Water supply and delivery in industry, construction sites and road works

TRICOFLEX® PERFORMANCE

+60
-20
°C



- 1 Soft PVC coating
- 2 Intermediate layer of flexible PVC yellow
- 3 Textile knitted reinforcement TNT
- 4 Intermediate layer of soft black PVC
- 5 Red flexible PVC

Five-layer knit water transport hose for professional use.



Marking: TRICOFLEX PERFORMANCE Tricoflex Non Torsion Technology [batch number]

ADVANTAGES

TRICOFLEX Performance combines high resistance and exceptional flexibility thanks to a multi-layered structure and an exclusive knit technique.

Resistant to abrasion, bad weather conditions, UV, crushing, and repeated pressure cycles, with a low curve radius preventing folding: these intrinsic qualities make the difference every day and for the long term.

TRICOFLEX Performance even has a red interior wall specially formulated to improve flow and resisted to polluted water, for a longer life span even in the case of especially tough use.

CONNECTORS

Connectors with band, screw or 'O' type clamps. Automatic connectors for watering.

CHEMICAL RESISTANCE

See table pages 102 to 105 column A.

mm	mm	mm	bar	bar	mm	Yellow	
						25 m	50 m
12,5	18,2	2,85	38	15	110	110000	110001
15	20,8	2,90	35	14	120	110002	110003
19	25,8	3,40	30	12	160	110004	110005
25	32,4	3,70	20	8	200	110006	110007